Konfigurace sítě, swap

Vytvořte soubor /etc/hostname s názvem počítače

```
echo myhostname > /etc/hostname
```

Toto je jedinečný název pro identifikaci vašeho zařízení v síti.

Přidejte odpovídající záznamy do /etc/hosts

```
nvim /etc/hosts
```

```
127.0.0.1 localhost
::1 localhost
127.0.1.1 myhostname
```

(Volitelné) Vytváření swap souboru

Nyní vytvořte prázdný (s velikostí 0) odkládací soubor. Vytvořte samostatný podsvazek pro odkládací soubor. Tento podsvazek je potřebný k tomu, abyste mohli vytvořit snímek /, což by nebylo možné s žádným souborem v něm s vypnutým CoW!

```
btrfs su create /swap
chattr +C /swap

# Copy on Write should always be disabled on swap file, so it will be done in the next step
```

```
touch /swap/swapfile

# Check if C attribute is enabled (should be already if created in folder with disabled CoW
attribute)
lsattr /swap/swapfile

# If not then disable CoW for swapfile manually
chattr +C /swap/swapfile

# Expanding empty file to 4GiB swap file
dd if=/dev/zero of=/swap/swapfile bs=1024K count=4096
chmod 600 /swap/swapfile

# Format the swap file.
mkswap /swap/swapfile

# Turn swap file on.
swapon /swap/swapfile

# You also need to update /etc/fstab to mount swapfile on boot
/swap/swapfile none swap sw 0 0
```

Revision #2
Created 2023-01-01 15:40:14 UTC by archos
Updated 2023-01-02 08:29:35 UTC by raven2cz